# HL   Baxtran

# Precision scale

Precision scales (10 mg) which combines beautiful and robust design with great functionality and easy use through the guide of the menus on display.

| U | FORM | PIP | PERCEN | RS232 | RS232 | AC/DC | NO VERIF |
|---|------|-----|--------|-------|-------|-------|----------|

## FEATURES:
- LCD backlight display, excellent display, with advanced eye protection.
- 8 digits of 15 mm in display with messages as a way to guide the user.
- 7 keys of direct functions.
- Superior frame in ABS and pan in stainless steel.
- Scale with a metal housing robust frame, for the protection against the causes of electrical storms and electromagnetic interferences.
- Four adjustable feet. They allow a greater stability, giving more precise results.
- Bubble level.
- Time of answer: 2-3 seconds.
- Multiple units of measure: gram, kilogram, pound, ounce, troy ounce, grain, pennyweight, carat, milligram, momme, mesghal, Hong Kong tael, Singapore taels, Taiwan taels, bath.
- Under weighing.
- Operating temperatura range:+15ºC +30ºC.
- Available models with internal calibration (HL-I).
- RS232, PC format and printer.
- 3 type of data sending to PC:
  - Continue: data sending in continue mode.
  - Ald: data sending to PC in stabilized weight.
  - Req: data sending to PC by user request.
- GLP/GMP.
- It is included dust cover and blister.

## FUNCTIONS
- Piece counting
- Determination of percentage
- Filter of weighing of animals
- Formulation
- Custom unite
- Control of weight
- Function of target weighing
- Determination of density
- Calibration of the pipette
- Statistics
- Totalization


RS232, Dual Display & Foot


Bubble level


Adjustable feet


Dimensions (mm)

342 / 211 / h100

| Precision | 260346 | 260348 | 260347 | 260349 |
|-----------|--------|--------|--------|--------|
| Type of cabin scale | - | | | |
| Multiple units | Yes | | | |
| CE regulations | Yes | Yes | Yes | Yes |
| Formulation | Max. number of weights that can be summed is 99 | | | |
| Type of calibration | External | External | Internal | Internal |
| Auto calibration | no | no | Yes | Yes |
| Mass of calibration g | 1500 (F1) | 2000 (F1) | 1500 (F1) | 2000 (F1) |
| Class | II | II | II | II |
| Net weight | 4,8 kg | | | |

| Code # | Internal calibration | Capacity (g) | Readout (g) | Pan dimensions (mm) | Packing dimensions (mm) | Packing weight (kg) | |
|--------|---------------------|--------------|-------------|---------------------|-------------------------|---------------------|--|
| 260346 | | 3100 | 0,01 | 198x205 | 500x410x330 | 7,5 | |
| 260348 | | 4100 | 0,01 | 198x205 | 500x410x330 | 7,5 | |
| 260347 | ☐ | 3100 | 0,01 | 198x205 | 500x410x330 | 7,5 | |
| 260349 | ☐ | 4100 | 0,01 | 198x205 | 500x410x330 | 7,5 | |

| Certifications |
|----------------|
| ENAC |

| Code # |
|--------|
| 900039 |
| 900039 |
| 900039 |
| 900039 |

| Accessories | |
|-------------|--|
| Code # | Accessories description |
| 910034 | IMP27 printer |
| 910035 | IMP28 printer |